


壓力 Pressure CLASS008-1500 PN16.8-26.0

- 雙開閘門雙層式閘板 雙層閘板閘門
Solex doublewooded doublepressure sealed bonnet
- 全閘
Full Port
- 雙邊閘板
Joint edge gate
- 雙止邊無坡式閘板
Flange without beveling ends

基本規格 Technical Specification

基本規格 Technical Specification	BSL/BSL/BSL/BSL	圖号 CODE
設計標準 Design Standard	ASME B16.34/BS1634	GB712204 GB712204
壓力/溫度 Pressure-Temperature Rating	ASME B16.34	GB712204
閘板材質 Gate-Plate	ASME B16.34	GB712204 JB7127-86
雙止邊式閘板 Flange Ends	ASME B16.34	BSPT120 JB7127-1-82-1
閘板密封面 Non-welding ends	ASME B16.34	GB712204
閘板/閘板 Flange & Tie	A1000	JB71200

主要尺寸及重量 Main Dimensions & Weight

壓力 Pressure	閘門尺寸 Gate Size		閘門尺寸 Valve Main Dimension							重量 Weight (kg)	
	mm	in.	閘板厚度 Gate	Lmm	Lin	Lmm	閘板厚度 Gate	H	H	閘板厚度 Gate	H
CLASS008-1500	10	1/2	15	170	236	236	190	200	120	1.2	15.0
	20	3/4	18	200	259	259	211	220	120	11.0	18.2
	25	1	24	254	294	294	238	250	160	11.0	21.2
	32	1-1/8	28	278	319	319	257	280	160	11.2	24.0
	40	1-1/2	32.5	305	345	345	278	300	160	12.0	28.2
PN16.8	10	1/2	13	170	170	1	190	200	120	1.2	15.0
	20	3/4	18	190	190	1	211	220	120	11.0	18.2
	25	1	24	230	230	1	238	250	160	11.1	21.2
	32	1-1/8	28	280	280	1	287	280	160	11.8	24.0
	40	1-1/2	32.5	300	300	1	278	300	160	12.3	28.0
PN26.0	10	1/2	13	170	170	1	190	200	120	1.2	15.0
	20	3/4	18	200	200	1	211	220	120	11.8	18.2
	25	1	24	254	254	1	238	250	160	11.8	21.2
	32	1-1/8	28	278	278	1	257	280	160	11.2	24.0
	40	1-1/2	32.5	300	300	1	278	300	160	12.4	28.2

註：H為閘門全開時的總高度 Note: H means the height after valve is fully opened.